


Instruction Manual

SB-800

High Performance Powered Subwoofer



Safety Precautions



CAUTION: To reduce the risk of electric shock, do not remove the cover (or back). No user serviceable parts inside. Refer to qualified personnel.

WARNING: To reduce the risk of fire or electric shock, do not expose this appliance to rain or moisture. This device generates a fair amount of heat. Make sure nothing blocks the ventilation openings on the top and bottom of the unit.



The lightning flash with arrowhead, within an equilateral triangle, is intended to alert the user to the presence of uninsulated "dangerous voltage" within the product's enclosure that may be of sufficient magnitude to constitute a risk of electrical shock to persons.



The exclamation point within an equilateral triangle is intended to alert the user to the presence of important operating maintenance (servicing) instructions in the literature accompanying the appliance.

For Future Reference

Record your serial numbers and date of purchase here:


Model Number			
Serial Number			
Date of Purchase			

The serial number is found on the back panel.

Model SB-800 Specifications

Bass Driver	8" long-throw	
Output Power	100W RMS	
Distortion (amplifier)	<0.5%	
Frequency Response	32Hz – 200Hz ±3 dB	
Peak Output	103dB SPL into 2000 cubic Feet	
Dimensions (WxHxD)	11 x 13 x 13 in; 280 x 330 x 330mm add 1.75" (45mm) H for feet add 1.5" (38mm) D for knobs & grille	
Weight	28lbs/12.7kg	
Power Requirements	110-120/220-240V, 50/60Hz, 250W Max	

SB-800 Subwoofer Rear Panel



1 Bass Level Control

Use this control to set the level of bass desired

2 Status LED

This will be green for "on" condition, amber for "standby"

(3) Standby Switch

When in ON position, the amplifier will always be on. When in the AUTO position, the amplifier will be in Automatic Standby Mode.

(4) Low-Pass Control

An adjustable (55Hz to 200Hz) @ 18dB per octave low-pass crossover.

(5) Phase Switch

This switch allows precise acoustic matching with satellite speaker systems whose output may be phase reversed. Try in both positions — use the position that results in the strongest bass output.

6 Low-Pass Switch

When in the LOW-PASS position, adjustment of the crossover can be made by the Crossover Control. If being fed a pre-filtered or THX signal, place the switch at the BYPASS position.

7 Low Level Output

The outputs allow daisy chaining of multiple subwoofers, or as a return path back to the processor.

(8) Low Level Input

Use the input to connect to the subwoofer or LFE line out from your processor/receiver.

9 Product Serial Number

Write this number in the space provided on page 2 for future reference.

10 Voltage Select Switch

Voltage switch for use in different countries. This switch will be set when you receive the unit. Change this setting only when you are sure your application requires it. For US, the switch should be set to the 115V position.

(11) On/Off Switch

Use this switch to turn the amplifier completely on or off.


(12) AC Input

Use the included power cord to connect your amplifier to a wall outlet.


Placement and Operation

Generally speaking, the best location for your new subwoofer is the front of the room, close to a corner (Figure 5). Every room has its own unique sound characteristics, and flexibility in the exact placement of the subwoofer is always desirable. The closer the subwoofer is placed to a wall and especially a corner, the more and deeper the bass response you will hear. However, in some rooms, corner placement can produce a "one note" boomy effect. Under such circumstances the subwoofer may work better away from the corner. Experiment to find the best position in your room.

Figure 5Typical arrangement for a single subwoofer in a home theater.



Using the Subwoofer Low-Pass Control



NOTE: Set this control to "Bypass" if you are using a receiver that has its own subwoofer crossover. Set this control to "Normal" if your electronics do not have a bass management function. The goal is to optimize the performance of the system by ensuring that the subwoofer and satellites produce a cohesive and well integrated sound "picture."

Most surround sound receivers and processors offer a choice of crossovers, typically between 60 Hz and 150 Hz. We recommend using the 100Hz setting when using small speakers such as those in the FS-7.0. Consult your electronics owner's manual for more details.

It's generally undesirable to have the main speakers and the subwoofer overlap too much. Larger speakers means a lower Low-pass crossover frequency, smaller speakers means a higher Low-pass crossover frequency. Consult the manufacturer's specified low frequency response for your main speakers to determine the appropriate Low-pass setting on your subwoofer. In the end, however, a little time spent experimenting will generally result in dramatically better bass response.

Care of Your Subwoofer

Your subwoofer is constructed from 5/8" Medium Density Fiberboard. MDF is a non-resonant material ideal for speaker system enclosures. To clean the cabinet you may use a soft cloth either dry or slightly dampened with clean water. Be careful not to wet the cabinet or allow any water to enter the cabinet seams. Avoid placing your speakers in direct sunlight or near a source of heat that may, over time, damage the finish.

Subwoofer Troubleshooting Guide

Once your subwoofer is set up, you should have many years of maintenance free enjoyment from your system. However, if you should encounter a problem, refer to the following guide to help you find the solution. If a problem persists, you should contact your local authorized Atlantic Technology dealer.

Problem	Possible Cause	Possible Solution	
No bass output	AC power cord unplugged or plugged into a non-working outlet.	Plug into a working outlet.	
	Input cables not securely connected or defective.	Check all connections, then try another input cable.	
Audible buzz or hum	Input cable not securely connected or defective.	Check all connections, then try another input cable.	
	Ground loop through antenna or cable TV system input.	Test by disconnecting antenna and/or cable system input leads. If hum goes away, install isolation balun(s) at that point.	